



SPECIFICATIONS

Product Description: **12" (30.4 cm) PLASTIC COM-PAX-IAL BLOWER AC**
 Part Number: **9543-E*, 9543-15E*, 9543-25E***
 Style: **AXIAL FAN 12" (30.4 cm) WITH OR WITHOUT CANISTER**

GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow. Available as blower only or complete unit with 15' (4.57 m) or 25' (7.62 m) of ducting and storage canister. Canister attaches to intake or output of blower for suction or ventilation.

CONSTRUCTION:

- Polyethylene housing and canister assembly
- Lightweight-, corrosion-, UV- and chemical-resistant
- Super quiet, in "safety orange" housing
- Carry handle molded into blower and canister housing
- Steel powder coated grill



MOTOR:

HP: 1 HP
 Certification: UL Listed, CSA Certified, CE Certified
 Voltage/Hz: 115V-230V AC, 50/60Hz, Single Phase, All World Motor
 RPM: 3400 (Loaded at 120 Volts, 60 Hz)
 Amps: 11A-5.5A (50 Hz), 10A-5A (60 Hz)
 Switch: Built in ON/OFF Rocker
 Cord: 13' (3.96 m) AWG



FAN:

- Polypropylene six blade fan

DUCTING: (included on 9543-15E and 9543-25E models)

- Retractable, non-collapsible design, Single-ply
- PVC coated vinyl and polyester materials
- Yellow color with black weather strip and integrated nylon attachment strap
- Spring steel wire helix

BLOWER DIMENSIONS:

Blower P/N	Length In. (cm)	Width In. (cm)	Height In. (cm)	Weight Lbs. (Kg)
9543-E	13" (33)	16" (40.6)	17" (43.1)	28 lbs (12.7)
9543-15E	27" (68.5)	16" (40.6)	17" (43.1)	43 lbs (19.5)
9543-25E	27" (68.5)	16" (40.6)	17" (43.1)	49 lbs (22.2)

****FLOW RATES:** (CFM calculated using 15' (4.57 m) of 12" (30.4 cm) ducting

Free Air CFM (m ³ /hr)	One 90° Bend CFM (m ³ /hr)	Two 90° Bends CFM (m ³ /hr)
1842 (3129.57)	1004 (1705.8)	933 (1585.17)

*Blowers offered in 220V/50 Hz

**Air flow determined at 60 Hz



SUCCESS UDYOG PVT. LTD.

Office: 315/316, 3rd Floor, CITY SPACE, Sr. No. 198/1A, Near CTR Industries, Vimannagar, Pune-Nagar Road, Pune-411014, Maharashtra, India.

Godown : Jadhav warehousing, Gat no. 1338/1, Priyankanagari, Wagholi, Pune – 411207

Godown Tel : 9370223874 Email: sales@successudyog.com Web: www.successudyog.com

Off. Tel : 020-40188288/244/221-226 Cell-9371919702 Fax: 020-40188227/299

GST NO. 27AAMCS0560N1ZW PAN No. : AAMCS0560N CIN U29193PN2008PTC132182