



SPECIFICATIONS

Product Description: **DUCTING,**
 Part Number: **9500-06, 9500-15, 9500-25**
 Style: **8" (20.3 cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.



CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- PVC Coated
- Temperature Range: -20°F to 180°F (-28.8°C to 82.22°C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Yellow color with black weather-strip
- Fastening cuffs at both ends

AVAILABLE:

Part No.	Diameter In (cm)	Length In (m)	End-Straps
9500-06	8" (20.3 cm)	6' (1.82 m)	Dual
9500-15	8" (20.3 cm)	15' (4.57 m)	Dual
9500-25	8" (20.3 cm)	25' (7.62 m)	Dual

ACCESSORIES:

Part No.	Ducting Size In (cm)	Description
9500-01	8" (20.3)	Duct to Duct Connector, with raised lip
9510-50	8" (20.3)	Manhole Ventilation Passthru, MVP
9500-35	8" (20.3)	Storage Rack for 8" (20.3 cm) Ducting, up to 25' (7.62 m) Ducting
9500-45	8" (20.3)	Storage Bag



SPECIFICATIONS

Product Description: **DUCTING, 12" (30.4cm) DIAMETER**
 Part Number: **9550-15, 9550-25**
 Style: **RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- PVC Coated
- Temperature Range: -20°F to 180°F (-28.8°C to 82.2°C)
- Retractable, Non-collapsible design
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Yellow color with black weather-strip
- Fastening cuffs at both ends



AVAILABLE:

Part No.	Diameter In. (cm)	Length Ft. (m)	End Straps	Weight Lbs. (Kg)
9550-15	12" (30.4 cm)	15' (4.57 m)	Dual	14 lbs. (6.3 kg)
9550-25	12" (30.4 cm)	25' (7.62 m)	Dual	22 lbs. (9.8 kg)

ACCESSORIES:

Part No.	Ducting Size	Description
9509-03	12" (30.4 cm)	Reduces 12" (30.4cm) blower to 8" (20.3cm) ducting (use only with 9509-50 blower)
9550-01	12" (30.4 cm)	Duct to Duct Connector, with raised lip
9600-36	12" (30.4 cm)	Storage Rack for 12" (30.4cm) Ducting, up to 25' (7.62m) Ducting
9600-45	12" (30.4 cm)	Storage Bag



SPECIFICATIONS

Product Description: **DUCTING,**
 Part Number: **9600-15, 9600-25**
 Style: **16" (40.6cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.



CONSTRUCTION:

- Vinyl and polyester materials
- Single-ply
- PVC coated
- Temperature range: -20°F to 180°F (-28.8°C to 82.2°C)
- Retractable, non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 specs
- UL 94V-0 flame retardant
- Yellow color with black weather-strip
- Fastening cuffs at both ends

AVAILABLE:

Part No.	Diameter In (cm)	Length Ft (m)	End-Straps
9600-15	16" (40.6 cm)	15' (4.57 m)	Dual
9600-25	16" (40.6 cm)	25' (7.62 m)	Dual

ACCESSORIES:

Part No.	Ducting Size	Description
9600-01	16" (40.6 cm)	Duct to Duct Connector, with raised lip
9600-35	16" (40.6 cm)	Storage Rack for 16"(40.6 cm) Ducting, up to 25' (7.62 m) Ducting
9600-45	16" (40.6 cm)	Storage Bag
9600-50	16" 40.6 cm) to 8"(20.3 cm)	Reducer from 16" (40.6 cm) blower to 8" (20.3 cm) ducting



SPECIFICATIONS

Product Description: **DUCTING,**
Part Number: **9650-15, 9650-25**
Style: **20" RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-ply
- PVC coated
- Temperature range: -20°F to 180°F
- Retractable, non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Steel wire meets ASTM 227 Specs.
- Yellow color with black weather-strip
- Fastening cuffs at both ends



AVAILABLE:

Part No.	Diameter	Length	End-Straps
9650-15	20" (50.8 cm)	15' (4.57 m)	Dual
9650-25	20" (50.8 cm)	25' (7.62 m)	Dual

ACCESSORIES:

Part No.	Ducting Size	Description
9650-01	20" (50.8 cm)	Duct to Duct Connector, with raised lip
9600-45	20" (50.8 cm)	Storage Bag



SPECIFICATIONS

Product Description: **DUCTING**
Part Number: **9700-15, 9700-25**
Style: **26" (66.0cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with minimum friction loss.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-ply
- PVC coated
- Temperature range: -20°F to 180°F (-28.8°C to 82.2°C)
- Retractable, non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 specs
- UL 94V-0 flame retardant
- Yellow color with black weather-strip
- Fastening cuffs at both ends



AVAILABLE:

Part No.	Diameter In (cm)	Length Ft (m)	End-Straps
9700-15	26" (66.0 cm)	15' (4.57 m)	Dual
9700-25	26" (66.0 cm)	25' (7.62 m)	Dual