SPECIFICATIONS

Product Description: CO MONITOR

Part Number: 9871-02 Style: REMOTE

GENERAL DESCRIPTION:

Attached to any air source or filter panel. To meet OSHA requirements an optional CO monitor is available for continuous monitoring of carbon monoxide levels. Panel provides up to 60 CFM of air within a 5-125 PSI range.

CONSTRUCTION:

• Housed in a portable, rugged Pelican case with handle and latches for protection and security.

• Airline pigtail & coupling kit for fast and easy adaptation to an existing air filtration system.

• All Brass Plumbing with Quick-Disconnect 1/4" *Hansen* plug.

CO MONITOR:

Power source: 115V AC to 9V DC power adapter for continuous power supply.

9V DC Alkaline battery (primary or as back-up for AC adapter).

Alarm Setting: 10 PPM (Canada: 5PPM)
External Connections: Optional Strobe Light Alarm.
Audible: 90 decibel Piezo Alarm.

Visual: External power LED light signal. Sensor: Electrochemical, Replaceable

Display: Liquid Crystal Keys: Mode & Set

Modes: Normal Operation, Peak, Battery Charge and Calibration mode.

Calibration: Self adjusting calibration to 20 PPM CO

REGULATOR:

- Pressure range (5-150psi)
- Zinc body & ABS cover
- Acetal adjusting knob
- Brass/Nitrile valve
- 0-160 pressure gauge

FLOW METER:

- Clear acrylic
- Teflon float
- Adjustable metering valve
- Graduations from 0.0-1.0 LPM



DIMENSIONS:

Length	Width	Height	Weight
12 "	5 "	10"	6.5 Lbs.



SUCCESS UDYOG PVT. LTD.

Registered Office: Office No. 315/316, 3rd floor, City Space, Sr.No.198/1A, Pune Nagar Road, Pune 411014, Maharashtra

 $\label{local-condition} {\bf Godown:} \ {\bf Jadhav warehousing,} \ {\bf Gat no.} \ {\bf 1338/1,} \ {\bf Priyankanagari,} \ {\bf Wagholi,} \ {\bf Pune-411207} \ {\bf Off.} \ {\bf Tel:} \ {\bf 020-40188288/216/244/221-228,} \ {\bf Cell-9371919702/9370223873} \ {\bf Fax:} \ {\bf 020-40188227/299} \ {\bf Value of the condition of the condi$

Email: sales@successudyog.com Web: www.successudyog.com